



VidyoGateway™

Flexible and Affordable Interoperability

Business Challenge

Enterprises have turned to video conferencing technology to enhance worker collaboration and efficiency. Many have made significant investments in video and voice conferencing systems but want to move to more modern platforms for higher quality collaboration. Enterprises demand high quality video conferencing technology that is flexible that works with existing legacy systems.

VidyoGateway delivers robust interoperability for third party voice and video conferencing systems

Quality matters.

Solution Overview

Enterprises are rapidly increasing the use of video conferencing technology for collaboration. This includes the use of newer technologies for desktop and mobile based video endpoints providing users with the flexibility to conveniently collaborate from anywhere. The VidyoConferencing™ platform delivers stunning video quality with robust reliability that enterprises demand. With the VidyoGateway™ enterprises can take full advantage of the VidyoConferencing platform while still leveraging investments made in legacy technology.

The VidyoGateway brings interoperability from third party voice and video systems into the VidyoConferencing platform. Meeting participants joining from third party H.323 and SIP based systems get full bidirectional audio and video capability along with advanced capabilities such as content sharing, far end camera control, encryption, DTMF controls, and more.

For IT managers, the VidyoGateway is easily deployed either as a turnkey network appliance or virtualized software package. The VidyoGateway provides numerous IT friendly features including clustering for increased capacity and redundancy, integration into third party call control, firewall/NAT traversal, and many more.

Exceptional User Experience

- Connect and control third party H.323 and SIP endpoints and cameras
- Share content between H.323, SIP and Vidyo endpoints
- Manage call the in-call experience through DTMF commands
- Customizable Interactive Voice Response (IVR), participant join/leave and recording indicators
- Receive the best call quality possible with automatic bit rate and resolution matching
- Easily connect to conferences with built in firewall and NAT traversal support

IT Benefits

- Automatically sizes capacity to allocated VM resources
- Clustering and high availability deployment options enhance capacity and resiliency
- Simplify administration, configuration and maintenance with centralized web-based interface
- Leverage built-in security management: SSL certificates, private key management, and HTTPS all FIPS 140-2 compliant

Specifications

	VidyoGateway™ XL	VidyoGateway™ VE					
Capacity	2x 1080p30 or 5x 720p30 15x SD 25x CIF 50x audio only	Resource Allocation	1080p	720p	SD	CIF	Audio
		2 GHz, 2GB RAM	N/A	1	2	4	10
		4.4GHz, 2GB RAM	1	2	4	8	20
		8.8GHz, 6GB RAM	2	4	9	15	50
		12GHz, 8GB RAM	3	5	12	25	75
		20GHz, 12GB RAM	4	8	18	50	100
		25GHz, 15GB RAM	5	10	20	50	125
Content Sharing	up to 1080p30	up to 1080p30					
Protocols and Standards	Video: H.264 SVC (UCIF mode 2s), H.264 AVC, H.263 Audio: G.711, G.722, Opus Signaling: H.323 and SIP Data Sharing: H.239, BFCP Encryption: SRTP, H.235 AES, and TLS Far-end Camera Control (FECC): H.224 Dialing: E.164, URI (H.323 Annex O and SIP URI) Firewall/NAT Traversal: RFCs 7362, 3581 and 5626						
Layouts	Gallery View, Continuous Presence, Active Speaker						
Power Supply	Input: 100-240v ~, 3.5A, 50-60Hz Output: 2x 550W Redundant (auto-ranging, Platinum efficiency) Consumption: 112W (idle), 210W (full load) Dissipation: 245 BTU (idle), 645 BTU (full load)	Hypervisor VMWare® ESXi 5.0 or higher (Enterprise Edition)					
Physical	Dimensions (HxWxD) without ear and bezel: Height: 1.69" (42.8 mm) Width: 17.09" (434.0 mm) Depth: 25.28" (642.3.1 mm) Weight: 43.87 lbs (19.9 kg) Form Factor: 1U Rack mount (ReadyRails™ sliding rails included)	Host Server Requirements Intel-based servers with a minimum Xeon 56xx Series at 2.4 GHz or faster, supporting Intel Westmere (or newer) architecture, with AES-NI and hyper-threading enabled; 1 Gbps NIC					
Network	2x RJ45 LAN ports: 100BASE-TX, and 1000BASE-T						
Environment	Operating Temperature Range: 10° to 35°C (50° to 95°F) Non-Operating Temperature Range: -40° to 70°C (-40° to 158°F) Operating Humidity Range: 8% to 90% non-condensing Non-Operating Humidity Range: 5% to 95% non-condensing						
Regulatory	NRTL Tested for Safety to the following Standard: UL 60950-1, 2nd Edition, 2014-10-14 (Information Technology Equipment - Safety - Part 1: General Requirements) CAN/CSA C22.2 No. 60950-1-07, 2nd Edition, 2014-10 (Information Technology Equipment - Safety - Part 1: General Requirements) Including the following additional standards: EN 60950-1:2006 + A11:2009 + A1:2010 + A12:2011 + A2:2013 (which includes all European national differences) EMC: Electromagnetic Emissions: FCC Class A, EN 55022 Class A, EN 61000-3-2/-3-3, CISPR 22 Class A Electromagnetic Immunity: EN 55024/ CISPR 24, (EN 61000-4-2, EN 61000-4-3, EN 61000-4-4, EN 61000-4-5, EN 61000-4-6, EN 61000-4-8, EN 61000-4-11)						



Vidyo, Inc. (Corporate Headquarters)
 433 Hackensack Ave., Hackensack, NJ 07601, USA
 Tel: 201.289.8597 Toll-free: 866.998.4396
 Email: vidyoinfo@vidyo.com

EMEA
 emea@vidyo.com
 +33 (0) 488 718 823

APAC
 apac@vidyo.com
 +852 3478 3870

INDIA
 india@vidyo.com
 +91 124 4111671